

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

COPY




0 JUN 1998

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E06B 1/34 // 3/38, E04D 13/02	A1	(11) International Publication Number: WO 98/22686 (43) International Publication Date: 28 May 1998 (28.05.98)
<p>(21) International Application Number: PCT/DK97/00515</p> <p>(22) International Filing Date: 13 November 1997 (13.11.97)</p> <p>(30) Priority Data: 1315/96 19 November 1996 (19.11.96) DK</p> <p>(71) Applicant (for all designated States except US): V. KANN RASMUSSEN INDUSTRI A/S [DK/DK]; Tobaksvejen 10, DK-2860 Søborg (DK).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): LINDGREN, Claes [DK/DK]; Lillevangsvej 37, DK-3520 Farum (DK).</p> <p>(74) Agents: CARLSSON, Eva et al.; International Patent-Bureau, Høje Taastrup Boulevard 23, DK-2630 Taastrup (DK).</p>	<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. In English translation (filed in Danish).</p>	

(54) Title: A WINDOW HAVING A WINDOW FRAME



(57) Abstract

In the window, which comprises a frame structure with top, bottom and side members (1-3) and a relative to the frame structure openable, top-hung sash structure with an insulating pane (4) encased between top, bottom and side members (5-7) of metal or plastic profiles, the insulating pane (4) is manufactured with dimensions corresponding to the exterior dimensions of the frame structure for direct abutment on a gasket (11-13) fastened to the exterior edge surfaces (17-19) of the top, bottom and side members of the frame structure. The top, bottom and side members of the frame structure comprise wood profiles with substantially parallelogram-shaped cross section, said exterior edge surfaces (17-19) being positioned in a common plane, with which the adjacent opposite side faces (26, 27) of the profile cross section form an angle (ν) of 95 to 140°.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A WINDOW HAVING A WINDOW FRAME

The present invention relates to a window, in particular for mounting in an inclined roof surface, comprising a frame structure with top, bottom and side members and a relative to the frame structure openable, top-hung sash structure with an insulating pane enchased between top, bottom and side members of metal or plastic profiles and manufactured with dimensions corresponding to the exterior dimensions of the frame structure for direct abutment on a gasket fastened to the exterior edge surfaces of the top, bottom and side members of the frame structure.

Windows of this type and of many different designs are among others known from DK Patent No. 74,858. In consideration of comfort and a general wish to save energy, big demands are made on among others the tightness and the insulating property of the window. On the other hand the manufacture of the window is to be rationally made without too many cost-increasing factors and with a cost-minded choice of material.

On this background the object of the invention is to provide a window which is both easy and cheap to manufacture, but which still meets the demand made in respect to insulating property, tightness, etc.

This object is according to the invention met by a window which is characterized in that the top, bottom and side members of the frame structure comprise wood profiles which have substantially parallelogram-shaped cross-sections, said exterior edge surfaces being positioned in a common plane, with which the adjacent opposite side faces of the profile cross-section form an angle of 95 to 140°.

By this embodiment the desired simple manufacture and good tightness between sash and frame are provided.

Furthermore, the parallelogram-shaped cross-section gives a higher stability in the corners of the frame structure than a rectangular cross-section of the same area. Furthermore, the parallelogram-shaped design of the wood profiles of the frame structure gives in combination with the big pane area an improved total light incidence compared with a window, in which the side surfaces of the frame structure extend perpendicularly to the sash plane. Furthermore, the advantage is obtained that exchange of accessories like roller blinds and insect nets is facilitated, as the access to the window is made easier on account of the oblique interior sides of the frame structure.

The wood profiles may be connected in profiled mitre joints, which in addition to making the mounting of the frame structure of the window simple provides an additional improvement of the insulation, the end faces of the wood profiles, which are badly insulating, being covered.

In view of a further saving of the expensive wood material, a preferred embodiment is characterized in that the thickness of the wood profiles is comparatively small and that for improving the heat insulating properties additional insulating elements of a good heat-insulating material are retained to the side of the profile cross-section which is intended to form the interior side for the top, bottom and side members of the frame structure.

The top, bottom and side members of the frame structure are on the interior side facing the light admitting area of the window covered by metal sheet profiles for providing a good heat transmission to border areas of the insulating pane. This heat transmission brings about a heating of the edge of the pane itself, whereby the formation of condensation is

considerably reduced relative to windows having a traditional "cold" pane edge.

The additional insulating elements preferably extend over a part of the width of the wood profiles
5 and are supported by abutment lists of wood connected with the wood profiles.

The above-mentioned reuse has been further improved in an embodiment, in which the top, bottom and side members of the frame structure with said addi-
10 tional insulating elements and possible heat-transmitting metal sheet profiles as a whole is connected solely by means of non-adhesive connection members in the mitre joints. In this way the window may be assembled by and large completely without separate
15 connection members and will consequently be easily dismountable with a view to reusing the various components of the window.

Further embodiments of the invention will appear from the remaining independent claims, which have not
20 been mentioned above.

The invention will be explained in the following with reference to an embodiment as shown in the accompanying drawing, in which

Fig. 1 is a perspective view of a top-hung window
25 to be mounted in an inclined roof surface,

Figs 2, 3 and 4 show a cross-section of the top, side and bottom members of the frame and sash structures along the lines II-II, III-III and IV-IV in Fig. 1,

30 Fig. 5 shows the design of a top hinge for the window, a lateral and partially sectional view of the sash, and

Fig. 6 the design of corner joints between the top, side and bottom members of the frame structure.

35 In the embodiment shown in the drawings, a top-

hung roof or skylight window according to the invention comprises a frame structure having a top member 1, side members 2 and a bottom member 3 and a top-hung sash structure openable relative thereto, in which an insulating pane 4 is enchased between a top member 5, side members 6 and a bottom member 7.

As will appear from the cross-sectional views in Figs 2-4, the insulating pane 4 is manufactured with dimensions which substantially correspond to the exterior measures of the frame structure, such that the edge surfaces 8-10 of the pane 4 are substantially flush with the exterior sides of the top, side and bottom members 1-3 of the frame structure, and such that the insulating pane 4 in the closed position of the window directly abuts resilient sealing profiles 11-13, which are retained in grooves 14-16 in exterior edge surfaces 17-19 of the top, side and bottom members 1-3 of the frame structure.

The sash profiles 5-7 are in the embodiment shown designed as metal sheet profiles with substantially L-shaped cross-section with a small wall thickness and mutually connected by corner joints 20, which, as shown in Fig. 1, may be made as 45° angular joints.

In this very simple and light sash structure, the insulating pane 4 is secured by an adhesive sealing, for instance, as shown, by joints 21 and 22 of silicone adhesive.

The wall 5a-7a of the L-shaped cross-section of the sash profiles 5-7, which abuts the edge surfaces 8-10 of the insulating pane 4, is, as shown, manufactured with such a width that in the closed position it overlaps the exterior side of the frame member 1-3 lying behind it and is at its interior edge folded for providing a softly rounded edge.

With a view to obtaining a good thermal insula-

tion, the top, side and bottom members 1-3 of the frame are made from wood profiles 23, which, as shown in Fig. 6, are connected at the corners in profiled mitre joints 24, for instance with undulating abutment surfaces 25. This method of joining has the advantage that it partly provides a safe mutual locking of the top, side and bottom members 1-3, partly gives optimum insulation properties, the end surfaces of the wood profiles being removed from the exterior sides of the frame members.

In the embodiment shown, the frame wood profiles 23 are manufactured with a substantially parallelogram-shaped cross-section, in which the above-mentioned exterior edge surfaces 17-19 lie in a common plane, with which the adjacent opposite side surfaces 26, 27 of the profile cross-section form an angle α of for instance 95 to 140°, in the embodiment shown 96°. By this profile cross-section, which provides the structure with the shape of a low frustum of a pyramid, an advantageous possibility is obtained of manufacturing the frame structure with oblique interior sides, which is desirable with a view to mounting various forms of accessories like for instance roller blinds and insect nets, and with a minimum consumption of material, the profiles 23 being, as shown, manufactured with a comparatively small thickness.

In the embodiment shown, the thermal insulation property of the frame structures is improved by the fact that to the side of the profiles 23, which is intended for forming the interior side of the frame structure, additional, substantially rod-shaped insulating elements 28 are retained, which may be manufactured from a suitable, well insulating material.

As will be seen from Figs 2-4, the insulating elements 28 extend across a part of the width of the

wood profiles 23 and are supported by abutment lists 29 connected with the wood profiles 23 by groove and tongue joints 30.

On the interior sides 26, the top, side and bottom members 1-3 of the frame structures end in a covering of metal sheet profiles 31, which covers the entire interior side and extends towards the edge area of the insulating pane 4. By this metal sheet covering such an improved heat transmission towards the insulating pane is obtained that in practice it has turned out to be possible to completely prevent condensation, something which otherwise frequently happens at the border areas of roof or skylight windows. The heat transmission typically has the effect that at a room temperature of 20°C and an outdoor temperature of 0°C, a temperature of about 14°C is obtained on the interior side of the insulating pane 4.

The fact that the abutment lists 29, as shown, are designed such that they at a distance from the wood profiles 23 form a nose portion 32, may be exploited for retaining the covering profile 31 by manufacturing it with a folded edge portion 33.

This design of the frame structure entails that the wood profiles 23 and the abutment lists 29 connected therewith may be releasably connected with the insulating elements 28 and the covering profiles 31, which can easily be exchanged for lacquering/change of colour or for mounting of fittings for accessories, and which entails a simple, and from an environmental point of view advantageous construction, which makes it possible at a subsequent dismounting to easily separate the frame structure into wood profiles, insulating elements and metal profiles with a view to reusing the materials to a high degree.

On the exterior sides the top, side and bottom

members 1-3 of the frame structure are in a manner known per se covered by flashing profiles 34-36 of metal sheets.

For fastening of the window to the underlying roof structure grooves 35a have, as shown in Fig. 3, been provided in the frame side members 2 for receiving fixing angles or straps, which are subsequently secured to the roof structure.

The sash and frame constructions shown makes it in an advantageous manner possible to make the top hinge of the window integral with the top members 1 and 5 of the frame and sash structures, respectively.

For this purpose a fitting member 37 with a hinge pin forming member in the form of a projecting wall portion 38 may be connected with the flashing profile 34 for the frame top member 1, whereas a substantially V-shaped hook member 39 is made integral with the wall portion 5a of the L-shaped metal sheet profile for the sash top member 5, said hook member 39 being hinged on the upward wall portion 38 and having an opening angle in the range of 20 to 30°.

To hold the hook member 39 and the projecting wall portion 38 in mutual engagement and to make a turning of the sash structure to a ventilation position possible, securing means have, as shown in Fig. 5, been secured to adjacent pairs of side members 2 and 6 of the frame and sash structures, said securing means comprising, in the embodiment shown, holding means 40 and 41, for instance in the form of blocks of a wear-resistant plastic material, with part-cylindrical guide surfaces 42 and 43 with axis in the pivot axis of the hinge 44. Within an opening angle range, which is smaller than the opening angle of the V-shaped hook member 39, the holding means 40 and 41 will keep the hinge members 38 and 39 in mutual engagement, whereas

they, when the sash structure is turned beyond this opening angle range to the position shown by a dotted line in Fig. 5, will be disengaged and thus allow an easy dismounting of the sash structure relative to the 5 frame structure.

For opening the sash structure relative to the frame structure to a ventilation position within the opening angle range, a window operator may in a manner known per se be mounted in connection with the bottom 10 members 3 and 7 of the frame and sash structures, for instance an electrically driven chain operator with an operator housing 45 accommodated in a recess in the wood profile 23 and the insulating element 28 and an operating chain 46, which may be detachably connected 15 with a sash fitting 47 secured to a for instance L-shaped console 48 in connection with the L-shaped sash profile 7a, for instance secured to its folded edge portion.

P A T E N T C L A I M S

1. A window, in particular for mounting in an inclined roof surface, comprising a frame structure with top, bottom and side members (1-3) and a relative
5 to the frame structure openable, top-hung sash structure with an insulating pane (4) enchased between top, bottom and side members (5-7) of metal or plastic profiles and manufactured with dimensions corresponding to the exterior dimensions of the frame structure for
10 direct abutment on a gasket (11-13) fastened to the exterior edge surfaces (17-19) of the top, bottom and side members of the frame structure, c h a r a c - t e r i z e d in that the top, bottom and side members of the frame structure comprise wood profiles (23) with
15 substantially parallelogram-shaped cross-sections, said exterior edge surfaces (17-19) being positioned in a common plane, with which the adjacent opposite side faces (26,27) of the profile cross-section form an angle (v) of 95 to 140°.

20 2. A window according to claim 1, c h a r a c - t e r i z e d in that said wood profiles (23) are connected in profiled mitre joints (25).

3. A window according to claim 2, c h a r a c - t e r i z e d in that the thickness of the wood
25 profiles (23) is comparatively small and that for improving the heat insulating properties additional insulating elements (28) of a good heat-insulating material are retained to the side of the profile cross-section which is intended to form the interior side for
30 the top, bottom and side members (1-3) of the frame structure.

4. A window according to claim 1, 2 or 3, c h a r - a c t e r i z e d in that the top, bottom and side members (1-3) of the frame structure on the interior
35 side facing the light admitting area of the window are

covered by metal sheet profiles (31) for providing a good heat transmission to border areas of the insulating pane (4).

5. A window according to claim 3, c h a r a c -
5 t e r i z e d in that the additional insulating elements (28) extend over a part of the width of the wood profiles (23) and are supported by abutment lists (29) of wood connected with the wood profiles.

6. A window according to claims 4 and 5, c h a r -
10 a c t e r i z e d in that said abutment lists (29) at the inwards facing edge side of the wood profiles (23) form a nose portion (32) for retaining a folded edge member (33) of the heat-transmitting metal sheet profiles (31), said nose portion being situated at a
15 distance from the adjacent inner side of the wood profiles.

7. A window according to one of the claims 3-6, c h a r a c t e r i z e d in that the top, bottom and side members (1-3) with said additional insulating
20 elements (28) and possible heat-transmitting metal sheet profiles (31) as a whole is connected solely by means of non-adhesive connection members in the mitre joints (24).

8. A window according to one of the claims 2-7,
25 c h a r a c t e r i z e d in that the outwards facing side faces of the top, bottom and side members (1-3) of the frame structure are covered by flashing profiles (34-36) of metal sheet.

9. A window according to claim 8, c h a r a c -
30 t e r i z e d in that a fitting member (37) is connected with the flashing profile (34) for the top member (1) of the frame structure, said fitting member having a projecting wall portion (38), which by engagement with a substantially V-shaped hook member (39)
35 integral with the top member (5) of the sash structure

forms a pivoting hinge for the sash structure relative to the frame structure.

10. A window according to claim 9, c h a r a c -
t e r i z e d in that holding means (40,41) are
5 fastened to at least one adjacent pair of the side
members (2,6) of the frame and sash structures, which
holding means, within a predetermined opening angle
range for the sash structure and calculated from the
closed position, hold the V-shaped hook member (39) and
10 said projecting wall portion (38) in mutual engagement,
but which, when turning the sash structure beyond said
opening angle range, allow removal of the sash struc-
ture from the frame structure.

HIS PAGE BLANK (USPTO)




FIG. 1

THIS PAGE BLANK (USPTO)




FIG. 2

THIS PAGE BLANK (USPTO)





FIG.3

THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)




FIG. 5




FIG. 6

THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 97/00515

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: E06B 1/34 // E06B 3/38, E04D 13/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: E06B, E04D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	CH 430138 C (ERNST SCHWEIZER METALLBAU, VORMALS J. SESSLER + CO.), 15 August 1967 (15.08.67) --	1
Y	SE 406787 B (ZANDA AB), 26 February 1979 (26.02.79) --	1
A	DE 3048961 A1 (FA. FRANZ BISPING), 1 July 1982 (01.07.82) --	1-10
A	DK 74858 C (W.B. KANN RASMUSSEN), 20 October 1952 (20.10.52) --	1-10

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

10 February 1998

Date of mailing of the international search report

13 -02- 1998

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Johan Winther

Telephone No. +46 8 782 25 00

2

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 97/00515

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4776141 A (J.W. POWELL), 11 October 1988 (11.10.88) -----	1-10

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/02/98

International application No.

PCT/DK 97/00515

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
CH	430138	C	15/08/67	NONE	
SE	406787	B	26/02/79	SE 7706368 A	02/12/78
DE	3048961	A1	01/07/82	NONE	
DK	74858	C	20/10/52	NONE	
US	4776141	A	11/10/88	NONE	

THIS PAGE BLANK (USPTO)